

# VALVE SPRING HIGHLIGHTS

## Introducing the NEW ML “MAX-LIFE” Super Endurance Roller Valve Spring Series

Designed for use in the most grueling, sustained Hi-RPM oval track environments, the “MAX-LIFE” super endurance series are manufactured from a revolutionary new alloy steel. They employ precision nitride heat treating and a multi-stage, micro-polished “MAX-LIFE” surface finish to enhance their longevity in the most aggressive endurance racing applications.



Part No.	Type	Outer OD/ID	Inner OD/ID	Seat Pressure	Open Pressure	Rate Per Inch	Coil Bind	Max. Net Lift
9987RADML	Dual w/Damper	1.570" / 1.146"	1.044" / .748"	275 lbs @2.000"	790 lbs @1.200"	644	1.150"	.800"
9996RADML	Dual w/Damper	1.600" / 1.150"	1.040" / .745"	275 lbs @2.050"	810 lbs @1.200"	625	1.150"	.850"
1511 (PSI)	Beehive LS	1.290" / .630"	—	130 lbs @1.800"	370 lbs @1.175"	384	1.100"	.625"
1516 (PSI)	Beehive LS	1.290" / .640"	—	150 lbs @1.800"	420 lbs @1.140"	409	1.080"	.660"
1542ML (PSI)	Dual	1.580" / 1.160"	— / .835"	248 lbs @2.050"	640 lbs @1.270"	503	1.200"	.780"
1574ML (PSI)	Dual	1.510" / 1.085"	— / .760"	180 lbs @1.980"	680 lbs @1.180"	625	1.110"	.800"
1575ML (PSI)	Dual	1.400" / .995"	— / .700"	150 lbs @2.000"	625 lbs @1.150"	559	1.100"	.850"
1577DML (PSI)	Dual w/Damper	1.550" / 1.100"	.985" / .706"	295 lbs @2.000"	860 lbs @1.200"	706	1.150"	.800"
1578ML (PSI)	Dual	1.378" / .976"	— / .680"	150 lbs @2.000"	640 lbs @1.150"	576	1.110"	.850"

We are proud to announce that Isky has recently been appointed a Distributor for PSI Sportsman Drag Race Valve Springs.

You can trust PSI (Performance Springs Inc.) Valve Springs to out-perform all others because they are exclusively 100% American Made using the finest materials, the best CNC Equipment and state of the art trade secret processing.

Don't settle for those foreign made springs of lesser quality. Insist on Genuine PSI Drag Race Valve Springs and get into the winners circle!

Isky Stocks the following PSI Part numbers.

Note: 1200 Series Springs utilize special Heat Treating and additional “Special Processing” for minimal load loss.



Valve Springs Specifications										
		(Tolerance = +/- .005)				Load Tolerance = +/- 3%				
		I.D.								
Part #	Type	O.D.	Outer	Middle	Inner	Seat Pressure	Open Pressure	Rate Per Inch	Max Net Lift	Coil Bind
1224	Dual	1.625"	1.175"	N/A	.855"	275 lbs @ 2.000"	750 lbs @ 1.200"	594	.800"	1.130"
425R	Dual	1.625"	1.175"	N/A	.855"	305 lbs @ 2.050"	865 lbs @ 1.150"	622	.900"	1.100"
1246	Triple	1.645"	1.195"	.870"	.630"	300 lbs @ 2.000"	890 lbs @ 1.200"	738	.800"	1.100"
1247	Triple	1.660"	1.195"	.870"	.630"	340 lbs @ 2.070"	940 lbs @ 1.270"	750	.800"	1.130"
1248	Triple	1.660"	1.195"	.870"	.630"	375 lbs @ 2.100"	1045 lbs @ 1.200"	744	.900"	1.130"
1249	Triple	1.660"	1.195"	.870"	.630"	385 lbs @ 2.200"	1110 lbs @ 1.200"	725	1.000"	1.130"
1250	Triple	1.660"	1.195"	.870"	.630"	395 lbs @ 2.250"	1178 lbs @ 1.200"	746	1.050"	1.130"



**ED ISKENDERIAN RACING CAMS**  
16020 S. BROADWAY GARDENA, CALIFORNIA 90247-9990  
(310) 217-9232 FAX (310) 515-5730

For the most up to date information on new products, visit us at our website: [www.iskycams.com](http://www.iskycams.com)