

**LOBE SPECIFICATION CHART**

**(OVAL TRACK ROLLER)**

TYPE OF CAM	LOBE LIFT	ADVERTISED DURATION	.050 DUR	.100 DUR	.200 DUR	.300 DUR	MASTER No.	Valve Lift With Zero Lash Rocker Arm Ratio		
								1.5	1.6	1.7
Oval Track Roller: Valve Lash Hot .028"	.376"	294 Deg.	260°	226°	173°	112°	R-561	.564"	.602"	.639"
	.376"	300 Deg.	266°	232°	177°	116°	R-562	.564"	.602"	.639"
	.376"	312 Deg.	278°	244°	186°	120°	R-559	.564"	.602"	.639"
	.393"	294 Deg.	260°	226°	174°	117°	R-555	.590"	.629"	.668"
	.393"	300 Deg.	266°	232°	180°	123°	R-503	.590"	.629"	.668"
	.393"	314 Deg.	280°	246°	192°	131°	R-560	.590"	.629"	.668"
	.400"	284 Deg.	252°	218°	168°	116°	R-582	.600"	.640"	.680"
	.400"	290 Deg.	256°	223°	172°	119°	R-554	.600"	.640"	.680"
	.400"	294 Deg.	260°	228°	176°	122°	R-548	.600"	.640"	.680"
	.400"	300 Deg.	266°	233°	181°	125°	R-534	.600"	.640"	.680"
	.400"	304 Deg.	270°	236°	184°	128°	R-533	.600"	.640"	.680"
	.400"	308 Deg.	274°	240°	187°	130°	R-479	.600"	.640"	.680"
	.410"	288 Deg.	254°	221°	172°	122°	R-514	.615"	.656"	.697"
	.410"	294 Deg.	260°	226°	177°	126°	R-494	.615"	.656"	.697"
	.410"	298 Deg.	264°	230°	181°	128°	R-553	.615"	.656"	.697"
	.410"	300 Deg.	266°	233°	183°	130°	R-571	.615"	.656"	.697"
	.411"	302 Deg.	268°	235°	185°	132°	R-493	.616"	.657"	.698"
	.411"	308 Deg.	274°	241°	189°	135°	R-515	.616"	.657"	.698"
	.420"	286 Deg.	254°	222°	174°	125°	R-558	.630"	.672"	.714"
	.420"	290 Deg.	258°	226°	177°	128°	R-581	.630"	.672"	.714"
	.420"	298 Deg.	264°	232°	183°	133°	R-556	.630"	.672"	.714"
	.420"	304 Deg.	268°	236°	185°	133°	R-590	.630"	.672"	.714"
	.420"	304 Deg.	270°	240°	188°	135°	R-535	.630"	.672"	.714"
	.420"	306 Deg.	272°	242°	190°	137°	R-651	.630"	.672"	.714"
	.420"	310 Deg.	276°	243°	191°	138°	R-467	.630"	.672"	.714"
	.420"	314 Deg.	280°	247°	194°	140°	R-469	.630"	.672"	.714"
	.420"	318 Deg.	282°	248°	195°	141°	R-470	.630"	.672"	.714"
	.430"	290 Deg.	256°	223°	175°	128°	R-586	.645"	.688"	.731"
	.430"	292 Deg.	258°	225°	177°	129°	R-661	.645"	.688"	.731"
	.430"	294 Deg.	260°	227°	178°	130°	R-575	.645"	.688"	.731"
.430"	296 Deg.	262°	229°	180°	132°	R-663	.645"	.688"	.731"	
.430"	298 Deg.	264°	231°	182°	133°	R-576	.645"	.688"	.731"	
.430"	302 Deg.	268°	234°	185°	136°	R-577	.645"	.688"	.731"	
.430"	306 Deg.	272°	238°	189°	138°	R-578	.645"	.688"	.731"	
.430"	310 Deg.	276°	243°	192°	141°	R-587	.645"	.688"	.731"	
Oval Track Roller: "Accelerator" Intake Profiles. Valve Lash Hot .024"	.433"	282 Deg.	252°	221°	175°	130°	R-627	.650"	.693"	.736"
	.433"	286 Deg.	256°	225°	179°	134°	R-625	.650"	.693"	.736"
	.433"	288 Deg.	258°	227°	181°	136°	R-667	.650"	.693"	.736"
	.433"	290 Deg.	260°	229°	183°	137°	R-624	.650"	.693"	.736"
	.433"	292 Deg.	262°	231°	185°	139°	R-668	.650"	.693"	.736"
	.433"	294 Deg.	264°	233°	187°	141°	R-623	.650"	.693"	.736"
	.433"	298 Deg.	268°	237°	191°	145°	R-626	.650"	.693"	.736"
.433"	302 Deg.	272°	241°	195°	149°	R-649	.650"	.693"	.736"	
Oval Track Roller Intake Valve Lash Hot .018"	.440"	290 Deg.	260°	228°	180°	132°	R-607	.660"	.704"	.748"
	.446"	294 Deg.	264°	234°	186°	139°	R-518	.670"	.713"	.758"

**ED ISKENDERIAN RACING CAMS**

16020 S. BROADWAY • BOX 30 • GARDENA, CALIFORNIA 90247-9990 • (323) 770-0930 • FAX (310) 515-5730

WWW.ISKYCAMS.COM

NOT LEGAL FOR SALE OR USE ON POLLUTION-CONTROLLED MOTOR VEHICLES